Printec

TRELLEBORG

Key Performance

- Sticky back blanket (adhesive-backed) for UV inks
- High print quality
- Resistance to chemical absorption and embossing
- Increased blanket lifetime
- Suitable for labels and envelopes printing
- Adhesive: clean and easy removal from the cylinder

MAIN APPLICATION

Business Forms and Labels

Printec 3336 is available in 3 ply 1,95 mm thickness



Printec 3336

The product at a glance

INK COMPATIBILITY	UV
PRINTING SURFACE COLOUR	Orange
THICKNESS (mm)	1,95
COMPRESSIBILITY (N/cm2)	138
SURFACE ROUGHNESS (µm)	1,0

FOR ANY FURTHER DETAILS AND FOR A QUOTATION PLEASE REFER TO YOUR SALES MANAGER OR EMAIL US AT: printingsm@trelleborg.com

www.trelleborg.com/printing

The information contained in this document is intended to provide guidance. The information is NOT a specification and all figures in the document are nominal. This document and the information it contains do not create any warranties for any product and Trelleborg Printing Solutions disclaims any warranty of merchantability or fitness for a particular purpose for the product described in this document. This document discloses information that is proprietary to Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce or disclose the document, any information contained in it, or any physical article or practice any method or process except by written agreement with Trelleborg Printing Solutions. Trelleborg Printing Solutions is committed to the ongoing development of its products. For that reason, Trelleborg Printing Solutions reserves the right to alter the actual specifications of its products without prior notice.