TRELLEBORG

Rollin

Key performance

- ·Consistent throw length, uniform nip pressure, easy washup
- The best adhesive in the market to avoid creeping and lifting
- ·Clean and easy removal from the cylinder
- Improved blanket lifetime

MAIN APPLICATION

Business Forms, labels Rollin Type150 is available in multiple ply type and multiple thickness



Rollin Type150

I

he product at a glance

INK COMPATIBILITY	UV	
PRINTING SURFACE COLOUR	Light Blue	
THICKNESS (mm)	0,90-0,94; 0,98-1,00; 1,04-1,06	
AVERAGE LOAD VALUE N/cm2 @ 0,23 mm Indentation	250	
SURFACE ROUGHNESS (Ra micron)	1,7	
ADDITIONAL INFORMATION		
BLANKET CONSTRUCTION	Adhesive	

FOR ANY FURTHER DETAILS AND FOR A QUOTATION PLEASE REFER TO YOUR SALES MANAGER OR EMAIL US AT: printingsm@trelleborg.com

www.trelleborg.com/printing

The information contained in this document is intended to provide guidance. The information is NOT a specification and all figures in the document are nominal. This document and the information it contains do not create any warranties for any product and Trelleborg Printing Solutions disclaims any warranty of merchantability or fitness for a particular purpose for the product described in this document. This document discloses information that is proprietary to Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce or disclose the document, any information contained in it, or any physical article or device, or to practice any method or process except by written agreement with Trelleborg Printing Solutions is committed to the ongoing development of its products. For that reason, Trelleborg Printing Solutions reserves the right to alter the actual specifications of its products without prior notice.