TRELLEBORG


Key performance

- Suitable for high speed newspaper presses
- Positive paper feed •
- Implements all benefits of the **Dynatech System**: •
 - Better vibration absorption
 - Less gears streaking marks
 - · Higher paper smash resistance
 - Blanket consistency
 - Excellent reboundability

MAIN APPLICATION

Coldset

Vulcan Editor 20 is available in 3 ply, 1,96 mm thickness



Vulcan Editor 20

The product at a glance

INK COMPATIBILITY	Hybrid
PRINTING SURFACE COLOUR	Blue
THICKNESS(mm)	1,96
AVERAGE LOAD VALUE N/cm2 @ 0,23 mm Indentation	250
SURFACE ROUGHNESS (Ra micron)	1,0
FEED FEATURES	Positive
ELONGATION (%)	<0,9
TENSILE STRENGTH (N/mm)	>67
WATER & SOLVENT PROTECTION	Yes
ADVANCED TECHNOLOGY	Dynatech
ADDITIONAL INFORMATION	
MORE VERSIONS	No Pack version available on demand

FOR ANY FURTHER DETAILS AND FOR A QUOTATION PLEASE REFER TO YOUR SALES MANAGER OR EMAIL US AT: printingsm@trelleborg.com

www.trelleborg.com/printing

The information contained in this document is intended to provide guidance. The information is NOT a specification and all figures in the document are nominal. This document and the information it contains do not create any warranties for any product and Trelleborg Printing Solutions disclaims any warranty of merchantability or fitness for a particular purpose for the product described in this document. This document discloses information that is proprietary to Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce or disclose the document, any information contained in it, or any physical article or device, or to practice any method or process except by written agreement with Trelleborg Printing Solutions. There are no printing Solutions of its products. For that reason, Trelleborg Printing Solutions reserves the right to alter the actual specifications of its products without prior notice.