## TRELLEBORG

## Key performance

(1)

- Specifically designed with the Feed-0 technology, which sets improved performance in terms of:
  - Optimum paper feed tension
  - Reduced risks of paper breaks
  - Easier control of colour register during the start-up
  - Improved paper wastage control
  - Improved paper release and reverse piling

## MAIN APPLICATION

**Commercial Web Heatset** 

Vulcan Mytho is available in 3 ply, 1,71 mm thickness



**Vulcan Mytho** 

The product	at a glance
-------------	-------------

INK COMPATIBILITY	Hybrid
PRINTING SURFACE COLOUR	Red
THICKNESS(mm)	1,71
AVERAGE LOAD VALUE N/cm2 @ 0,23 mm Indentation	250
SURFACE ROUGHNESS (Ra micron)	0,8
FEED FEATURES	Neutral
ELONGATION (%)	<0,9
TENSILE STRENGTH (N/mm)	>60
WATER & SOLVENT PROTECTION	Yes
ADDITIONAL INFORMATION	
PRESS FORMAT	Also suitable for large size presses

FOR ANY FURTHER DETAILS AND FOR A QUOTATION PLEASE REFER TO YOUR SALES MANAGER OR EMAIL US AT: printingsm@trelleborg.com

www.trelleborg.com/printing

The information contained in this document is intended to provide guidance. The information is NOT a specification and all figures in the document are nominal. This document and the information it contains do not create any warranties for any product and Trelleborg Printing Solutions disclaims any warranty of merchantability or fitness for a particular purpose for the product described in this document. This document discloses information that is proprietary to Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce or disclose the document, any information contained in it, or any physical article or device, or to practice any method or process except by written agreement with Trelleborg Printing Solutions. There are no printing Solutions of its products. For that reason, Trelleborg Printing Solutions reserves the right to alter the actual specifications of its products without prior notice.