# TRELLEBORG

#### **Key Performance**


Printec

- · Polyester base ensures dimensional stability
- Superior level of gloss
- ·Compatible with UV and aqueous coatings
- · Eliminate issues of coating build up
- · Dimensionally stable, ideal for repeated jobs
- · Easy to cut by hand or with CAD tables

### MAIN APPLICATION

#### Coating

Printec 194 is available fabric 2 ply + polyester 1,98 mm thickness



Printec 194

## The product at a glance

INK COMPATIBILITY	Aqueous and UV
PRINTING SURFACE COLOUR	Blue
THICKNESS (mm)	1,98
SURFACE	Rubber
SURFACE ROUGHNESS RA (micron)	0,6
CARRIER	Polyester
CARRIER THICKNESS (NM)	0.35
CUTTING DEPTH (mm)	0.8
ADDITIONAL INFORMATION	
APPLICATIONS	Coating

FOR ANY FURTHER DETAILS AND FOR A QUOTATION PLEASE REFER TO YOUR SALES MANAGER OR EMAIL US AT: printingsm@trelleborg.com

www.trelleborg.com/printing

The information contained in this document is intended to provide guidance. The information is NOT a specification and all figures in the document are nominal. This document and the information it contains do not create any warranties for any product and Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce product described in this document. This document discloses information that is proprietary to Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce or disclose the document, any information contained in it, or any physical article or device, or to practice any method or process except by written agreement with Trelleborg Printing Solutions is committed to the ongoing development of its products. For that reason, Trelleborg Printing Solutions reserves the right to alter the actual specifications of its products without prior notice.