TRELLEBORG



Key performance

- Specifically designed for currency printing and metal printing
- Perfect solid printing and ink transfer
- Suitable for fine details reproduction
- Very robust carcass to provide stability on press

MAIN APPLICATION

Currency Printing, Security

Vulcan Solid is available in 3 ply, 1,70 mm thickness



Vulcan Solid

The product at a glance

| INK COMPATIBILITY | Conventional |
|-------------------------------|---|
| PRINTING SURFACE COLOUR | Light Blue |
| THICKNESS (mm) | 1,70 |
| SURFACE ROUGHNESS (Ra micron) | 1,25 |
| ELONGATION (%) | <0,9 |
| TENSILE STRENGTH (N/mm) | >60 |
| WATER & SOLVENT PROTECTION | Yes |
| ADDITIONAL INFORMATION | |
| SURFACE | Micro Buffed printing surface finishing |

FOR ANY FURTHER DETAILS AND FOR A QUOTATION PLEASE REFER TO YOUR SALES MANAGER OR EMAIL US AT: printingsm@trelleborg.com

www.trelleborg.com/printing

The information contained in this document is intended to provide guidance. The information is NOT a specification and all figures in the document are nominal. This document and the information it contains do not create any warranties for any product and Trelleborg Printing Solutions disclaims any warranty of merchantability or fitness for a particular purpose for the product described in this document. This document discloses information that is proprietary to Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce or disclose the document, any information contained in it, or any physical article or device, or to practice any method or process except by written agreement with Trelleborg Printing Solutions. There are no printing Solutions of its products. For that reason, Trelleborg Printing Solutions reserves the right to alter the actual specifications of its products without prior notice.