



### Key performance

- Suitable for both conventional and UV inks
- Increased blanket lifetime
- Reduced downtime due to less blanket changes
- Improved Ink release and cleaning

### MAIN APPLICATION

Sheetfed, Packaging

**Printec 134-B is available in 3 ply, 1,96 mm thickness**



**Printec 134-B**

### ✓ The product at a glance

<b>INK COMPATIBILITY</b>	Hybrid
<b>PRINTING SURFACE COLOUR</b>	Blue
<b>THICKNESS (mm)</b>	1,96
<b>AVERAGE LOAD VALUE N/cm2 @ 0,23 mm Indentation</b>	240
<b>SURFACE ROUGHNESS (Ra micron)</b>	1,2
<b>ELONGATION (%)</b>	<0,9
<b>TENSILE STRENGTH (N/mm)</b>	>60
<b>WATER &amp; SOLVENT PROTECTION</b>	No
<b>ADDITIONAL INFORMATION</b>	
<b>APPLICATIONS</b>	All-round sheetfed blanket

**FOR ANY FURTHER DETAILS AND FOR A QUOTATION  
PLEASE REFER TO YOUR SALES MANAGER  
OR EMAIL US AT: [printingsm@trelleborg.com](mailto:printingsm@trelleborg.com)**